

HC-T2200N3-SL



Product Features

- ≥ 1/2.7" 2 Megapixel CMOS
- ≥ 25/30fps@1080P, 25/30/50/60fps@720P
- ≥ High speed, long distance real-time transmission
- ≥ HD and SD switchable
- ≥ Control over coaxial cable
- ≥ DWDR, Day/Night(ICR), AWB, AGC, BLC, 2D/3D-DNR
- ≥ 3.6mm fixed lens
- ≥ Max. IR LEDs length 30m, Smart IR
- ≥ IP67, DC12V



An ISO 9001:2008 Certified Company

Specifications :

Image Sensor	1/2.7" 2 Megapixel CMOS
Effective Pixels	1920(H) x 1080(V)
Electronic Shutter Speed	1/25 ~ 1/100000s
Minimum Illumination	0.02Lux/F2.0, 0Lux IR on
Synchronization	Internal
Video Output	1-channel BNC high definition video output/ CVBS Standard definition video output (can switch)
Max. IR LEDs Length	30m, 2PCS 3600K soft Warm light
Backlight Compensation	DWDR
Day/Night	Auto(ICR) / Color / B/W
Noise Reduction	2D/ 3D DNR
OSD Menu	OSD (COC Control)
Focal length	3.6mm, horizontal field of view: 89.9° 6mm, horizontal field of view: 56°
Mount Type	M12
Power Supply	DC12V±25%
Power Consumption	Max 4W
Working Environment	-40°C~+60°C / Less than 95% RH (non-condensation)
Transmission distance	Over 500m Via 75-3 coaxial cable
Ingress Protection	IP67
Material	Metal
Dimensions	_63mmx65mmx185mm
Weight	0.35kg

