

HD-NVR-5108Q



Product Features

- ≥ Support Smart H.265/H.265/H.264 video formats
- ≥ 8-channel input
- ≥ Support mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols
- ≥ Support 1-ch HDMI, 1-ch VGA, HDMI at up to 4K(3840x2160) resolution
- ≥ HDMI and VGA simultaneous output
- ≥ Up to 4K resolution recording
- ≥ 1 SATA HDD up to 8TB
- ≥ Support cloud upgrade



An ISO 9001:2008 Certified Company

Specifications :

VIDEO/AUDIO INPUT

IP Video Input 8-ch

NETWORK

Incoming Bandwidth 64Mbps

Outgoing Bandwidth 48Mbps

Remote Users 128

Protocols TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SMTP, RTSP

VIDEO/AUDIO INPUT

HDMI/VGA Output HDMI:
3840x2160/30Hz, 1920x1080/60Hz, 1920x1080/50Hz,
1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz,
1024x768/60Hz

VGA:
1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz,
1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz

Recording Resolution 4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

Audio Output 1-ch, 3.5mm

Audio Compression G.711A, G.711U

Synchronous Playback 8-ch

Liveview display 1/4/6/8/9

Corridor Mode Screen 3/4/5/7/9

SNAPSHOT

FTP/Schedule/Event Snapshot 1-ch snapshot, up to D1 resolution



An ISO 9001:2008 Certified Company

DECODING

Decoding format	Smart H.265/H.265/H.264
Liveview/Playback	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	1 x 4K@30, 4 x 5MP@25, 4 x 4MP@25, 4 x 3MP@25, 4 x 1080p@30, 8 x 720p@30

HARD DISK

SATA	1 SATA interface
Capacity	Up to 8TB for each disk (The maximum HDD capacity varies with environment temperature)

SMART

VCA Detection by Camera	Intrusion Detection, Line Crossing Detection, Enter Area, Leave Area, Audio Detection
VCA Search	Face Search, Behavior Search

GENERAL ALARM

General Alarm	Motion, Tampering, Human Body Detection, Video Loss, Alarm Input
Alert Alarm	IP Conflict, Network Disconnected, Disk Offline, Disk Abnormal, Illegal Access Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal

EXTERNAL INTERFACE

Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel: 2 x USB2.0



An ISO 9001:2008 Certified Company

GENERAL

Power Supply

12V DC

Power Consumption: ≤5 W (without HDD)

Working Environment

-10°C ~ + 55°C (+14°F ~ +131°F),

Humidity ≤ 90% RH (non-condensing)

Dimensions (W×D×H)

260mm × 240mm × 46mm (10.2"×9.4"×1.8 ")

Weight (without HDD)

≤0.98kg (2.16 lb)



An ISO 9001:2008 Certified Company